



LP7621

Floor Scale With Frame

※ Dimensions:

◆Unit (mm)




※ Technical Parameters

- ◆ Accuracy class: Ⅲ
- ◆ Display: 6-digit 20mm LED or 25mm LCD with backlight
- ◆ Work environment: -10° C ~+40° C , ≤ 85%RH
- ◆ Power Supply: AC110/220V 50/60Hz, Built-in battery DC4V/4Ah


※ Structural Features

- ◆ U shape steel structure
- ◆ Material: carbon steel or 304 stainless steel flat panel
- ◆ Carbon steel scales: Integral shot blasting or galvanizing
- ◆ All round shot 304 stainless steel
- ◆ 4 stainless steel load cell

※ Product Functions:



※ Various Scale:



※ Types & Specifications :

Item No.	Capacity	A	B	C	D	Weight (kg)	Ctn size (m)
LP7621-1010-1~3t	1~3t	1000	1000	6	92	105	1.03*1.03*0.08
LP7621-1010-5t	5t	1000	1000	6	92	110	1.03*1.03*0.08
LP7621-1012-1~3t	1~3t	1000	1200	6	92	118	1.03*1.23*0.08
LP7621-1012-5t	5t	1000	1200	6	92	135	1.03*1.23*0.08
LP7621-1212-1~3t	1~3t	1200	1200	6	92	130	1.23*1.23*0.08
LP7621-1212-5t	5t	1200	1200	6	92	145	1.23*1.23*0.08
LP7621-1215-1~3t	1~3t	1200	1500	6	92	155	1.23*1.53*0.08
LP7621-1215-5t	5t	1200	1500	6	92	170	1.23*1.53*0.08
LP7621-1515-1~3t	1~3t	1500	1500	6	92	185	1.53*1.53*0.08
LP7621-1515-5t	5t	1500	1500	6	92	205	1.53*1.53*0.08
LP7621-1520-1~3t	1~3t	1500	2000	6	92	230	1.53*2.03*0.10
LP7621-1520-5t	5t	1500	2000	6	100	260	1.53*2.03*0.10
LP7621-1520-10t	10t	1500	2000	8	135	350	1.53*2.03*0.15
LP7621-1530-1~3t	1~3t	1500	3000	6	100	350	1.53*3.03*0.10
LP7621-1530-5t	5t	1500	3000	6	105	410	1.53*3.03*0.15
LP7621-1530-10t	10t	1500	3000	8	135	530	1.53*3.03*0.15
LP7621-2020-10t	10t	2000	2000	8	135	470	2.03*2.03*0.15
LP7621-2030-10t	10t	2000	3000	8	135	720	2.03*3.03*0.15
LP7621-2040-10t	10t	2000	4000	8	135	860	2.03*4.03*0.15

LP7621NN: Carbon Steel Construction

LP7621NS: Carbon Steel Structural Stainless steel

LP7621SS: Stainless Steel architecture